



# Low Temperature Chest Freezer

0°C to -25°C

We offer wide range of sizes for Low Temperature Chest Freezer, all complete with product features most requested by the laboratory and medical industry. We offer quality selection to meet the specific needs of research laboratories, hospitals, pharmacies, veterinary offices, medical clinics, and other facilities with high demands for stable, low temperature storage.

### Features:

- ✓ Precise microcomputer temperature control
- ✓ Simple to operate
- ✓ Auto-defrost
- ✓ Forced-air circulation for enhanced temperature distribution
- ✓ Easy-to-read LED temperature display
- ✓ Visual and audible alarm alerts
- ✓ Low-noise compressor
- ✓ Large temperature ranges for storing goods: from 0°C to -25°C



VF 25H-100 / 200



VF 25H-300



VF 25H-560



VF 25H-300(S) / 500(S) / 1500(S)

Model	VF 25H-100	VF 25H-200	VF 25H-300	VF 25H-560	VF 25H-300(S)	VF 25H-500(S)	VF 25H-1500(S)
Dim. Ext (mm) W x D x H	560 x 485 x 830	940 x 550 x 845	1055 x 750 x 835	1655 x 750 x 835	1760 x 710 x 865	2160 x 760 x 855	2950 x 1065 x 865
Dim. Int (mm) W x D x H	430 x 360 x 690	840 x 450 x 700	930 x 530 x 700	1530 x 530 x 700	1000 x 430 x 710	1350 x 520 x 710	2185 x 915 x 710
Capacity	100L	200L	300L	560L	300L	500L	1,500L
Internal Chamber	Aluminium				Stainless Steel		
External Chamber	Mild Steel				Stainless Steel		
Input Power	100W	100W	300W	380W	300W	380W	1200W
Door Lock	1 no.	1 no.	1 no.	1 no.	1 no.	1 no.	1 no.
Temp. Controller	Digital	Digital	Digital	Digital	Digital	Digital	Digital
Castor	Nil	4 nos.	4 nos.	4 nos.	4 nos.	4 nos.	4 nos.
Internal Air Circulation	Direct						
Refrigerant CFC	R134a						
Power Voltage	220Vac 50Hz Single Phase (60Hz for others)						
Alarm System							
- Hi/Low Alarm	✓	✓	✓	✓	✓	✓	✓
Safety Features & Certification	ISO 13485, Electric Safety Test (EST) IEC 61010-1 (2010), GDPMD, ISO IEC 17025						