



ETS Blast Refrigerator

Model **VC 45B-2100 (F)** Capacity **2,100L** Temperature Range **+2°C to -40°C/-75°C (Adjustable)**



Dim. Ext. (mm) W x D x H	1300 x 1320 x 2190
Dim. Int. (mm) W x D x H	800 x 1050 x 1840
Temperature controller	LED Digital Microprocessor
Temperature Pull Down Rate	From ambient temperature to -40°C within 20 mins when first start
Auto Switch Off	Timer auto switch off to end program blast chilling
Internal & External Chamber	Stainless Steel
Temperature Controller	LED Digital Display
Temperature Fluctuation	±2.0°C
Body Insulation	100mm THK
Internal Cooling System	3 x 20" Evaporator Fan Motor
Condensing Unit	Condenser Fan Motor (2 x 20")
Tray Size (mm)	W630 x D700 x H60
No. of Trolley	2 nos.
No. of Tray(s)	15 pcs x 2nos. = 30pcs
Door Open Fan Switch	Fan stops when door opens
Refrigerant	R507 HCFC
Comp. Recip. Hermetic	7.7kW x 1 no.
Door Lock / Castor	2 nos. / 4pcs
Power Supply	415Vac 50Hz 3-Phase
Standard LED Alarm	Hi/Low Alarm, Power Failure
Standard complied with IEC 60601, Electrical Safety and ISO 13485, GDPMD	

No. 32-G & 32-1, Dataran Mestika, Jalan Mawar 17, Taman Mestika, 56100 Kuala Lumpur, Malaysia.

Tel: +603 – 4292 2722 / 4288 2722 Fax: +603 – 4293 2722

Email: etsbiofr@gmail.com / info@etsbiofreeze.com Website: www.etsbiofreeze.com