



# Low Temperature Chest Freezer

-0°C to -25°C

We offer wide range of sizes for Low Temperature Chest Freezer, all complete with product features most requested by the laboratory and medical industry. We offer quality selection to meet the specific needs of research laboratories, hospitals, pharmacies, veterinary offices, medical clinics, and other facilities with high demands for stable, low temperature storage.

## Features:

- ✓ Precise microcomputer temperature control
- ✓ Simple to operate
- ✓ Optimized evaporation system and condensation system, strong cooling, low energy consumption.
- ✓ Visual and audible alarm alerts
- ✓ Low-noise compressor
- ✓ Large temperature ranges for storing goods: from -10°C to -40°C



VF 25H-100 / 200



VF 25H-300



VF 25H-400/560



VF 25H-1500

Model	VF 25H-100	VF 25H-200	VF 25H-300	VF 25H-400	VF 25H-560	VF 25H-1500
Dim. Ext (mm) W x D x H	570 x 550 x 845	940 x 550 x 845	1055 x 750 x 835	1530 x 765 x 880	1655 x 750 x 835	2950 x 1065 x 865
Dim. Int (mm) W x D x H	430 x 360 x 690	840 x 450 x 700	930 x 530 x 700	1330 x 470 x 600	1530 x 530 x 700	2185 x 915 x 710
Capacity	100L	200L	300L	400L	560L	1,500L
Internal Chamber	Aluminium	Aluminium	Aluminium	Stainless Steel	Aluminium	Stainless Steel
External Chamber	Mild Steel	Mild Steel	Mild Steel	Epoxy Coated Mild Steel	Epoxy Coated Mild Steel	Stainless Steel
Input Power	100W	100W	300W	380W	380W	1200W
Door Lock	1 no.	1 no.	1 no.	1 no.	1 no.	1 no.
Temp.Controller	Digital	Digital	Digital	Digital	Digital	Digital
Castor	Nil	4 nos.	4 nos.	4 nos.	4 nos.	6 nos.
Internal Air Circulation	Direct					
Refrigerant CFC	R134a					
Power Voltage	220Vac 50Hz Single Phase (60Hz for others)					
Alarm System						
- Hi/Low Alarm	√	√	√	√	√	√
Safety Features & Certification	ISO 13485, Electric Safety Test (EST) IEC 61010-1 (2010), GDPMD, ISO IEC 17025					

- **NOTE : VC 25H-1500(F) WITH MDA CLASS A CERTIFICATE**
- **Capacity may vary according to the loading preferences and contents. Can be customized**