



Pharmaceutical Refrigerators

+2°C to +8°C (adjustable) | Single-door

ETS Pharmaceutical Refrigerators and freezers are designed and fabricated to meet the demanding requirements of scientific and laboratory applications. These refrigerators and freezers provide complete and integrated solutions for pharmaceuticals, medicines, biological products and reagents, etc. Suitable for pharmacy, laboratories, drug stores, research centres, pharmaceutical factories/companies, hospitals, clinics, healthcare, epidemic prevention centres, etc. Wide ranges of models are offered to accommodate your needs and requirements.

Features:

- ✓ User-friendly design
- ✓ Precise microcomputer temperature control
- ✓ Standard alarms and safety features
- ✓ Forced-air circulation for enhanced temperature stability
- ✓ Easy-to-read LED temperature display
- ✓ Visual and audible alarm alerts
- ✓ Low-noise compressor



Model	VC 130	VC 200 (D)	VC 500	VC 600	VC 800
Dim. Ext (mm) W x D x H	650 x 525 x 1350	580 x 750 x 1800	640 x 800 x 2070	700 x 800 x 2070	790 x 810 x 2245
Dim. Int (mm) W x D x H	430 x 400 x 790	430 x 400 x 586	540 x 650 x 1430	640 x 640 x 1430	660 x 720 x 1670
Capacity	130L	200L	500L	600L	800L
Int. Chamber	Stainless Steel 304 (Chemical resistance)	Stainless Steel 304	Epoxy Coated Mild Steel	Epoxy Coated Mild Steel	Epoxy Coated Mild Steel
Ext. Chamber	Stainless Steel 304 (Chemical resistance)	Epoxy Powder Coated	Epoxy Coated Mild Steel	Epoxy Coated Mild Steel	Epoxy Coated Mild Steel
Shelves (hold 50kg)	2pcs	4pcs	5pcs	5pcs	5pcs
Temp. Controller	Temp adjustable, LED display				
Temp Fluctuation	±1.0°C				
Internal Air Circulation	Forced-air				
Refrigerant	R134a CFC Free				
Glass Door	Single Heated Glass Door				
Door Lock / Castor	1 no. / 4 nos	2 nos. / 4 nos.	1 no. / 4 nos.	1 no. / 4 nos.	1 no. / 4 nos.
Comp. Recip. Hermetic	1/4 HP	1/3 HP	1/2 HP	1/2 HP	1/2 HP
Power Voltage	230Vac 50Hz Single Phase (60Hz for others)				
Standard LED Alarm System					
- Hi/Low Alarm	✓	✓	✓	✓	✓
- Remote Alarm Contact	✓	✓	✓	✓	✓
- Power Failure	✓	✓	✓	✓	✓
- 72-hour DC backup	✓	✓	✓	✓	✓
* Accessories (Optional)	Door Fan Switch				
Safety Features & Certification	ISO 13485, Electric Safety Test (EST) IEC 61010-1 (2010), GDPMD, ISO IEC 17025				

- **Optional Item : Touchscreen controller**